



KoskiLNG

N096 specially designed for LNG carriers

In the harsh climatic conditions of Finland trees have a short growing season. The growth is slow and the annular rings are narrow. The result is wood that is strong, homogeneous and of a consistently high quality.

Koskisen plywood boards are composed of thin Finnish Birch veneers glued together under pressure with the grain direction of the successive layers alternating at right angles.

Finnish birch is an ideal raw material for demanding speciality plywood applications; it can be used at sustained temperatures as low as -200 °C. and can thus be used in the thermal insulation structures of LNG vessels.

Key benefits

-  High strength properties
-  Good dimensional stability in extremely cold conditions
-  Strong Finnish birch as a raw material
-  Renewable material




ECO-FRIENDLY



COLD RESISTANT



CORE VENEERS QUALITY



EASY MACHINING

Technical specifications – KoskiLNG

Base plywood	Koskisen Finnish birch plywood
Bonding	Phenolic resin according to EN 314-2/ class 3 exterior conditions Formaldehyde emission levels of panels fulfil requirements of Class E1 (EN13986), CARB Phase II, ULEF (Ultra Low Emitting Formaldehyde)
Face qualities	Birch BB,WG
Standard thicknesses	6.5, 9, 12, 15, 21, 24, 30, 35 mm.
Standard sizes	1200/1220/1250 x 2400/2440/2500 mm 1200/1220 x 3000/3300/3600/4000 mm 1500/1525 x 3000/3300/3600/4000 mm Available as readymade cut to size components
Density	Approx 700 kg/m ³
Thermal Deformation	Plywood has excellent dimensional stability; in practice, the thermal deformation of plywood is so small, that it can generally be disregarded.
Machining	Drilling of holes edge machining like T&G, chamfer and rebate on request.
Other data	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit koskisen.com/download .

Additional information

Environment

Our raw material, wood is an ecological and renewable material and it stores carbon during its whole life cycle. Koskisen plywood products are manufactured in Finland according to the strictest sustainability principles. Koskisen is a pioneer in the Finnish forest industry in paying attention to the environment and the wood's supply chain is always known in detail. Finnish forests are primarily privately owned and the owners are guided by a strong commitment to long-term forestry and forest cultivation. Yearly, Finnish forests grow more than they are harvested. This guarantees a sustainable and environmentally sound raw material.

Additional information

Wood is a living material and every panel is unique. Therefore a photograph or a sample piece cannot represent a full sized panel as regards colours, shades, figure, knots etc. Please note that a slight colour variation is accepted between panels.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.

Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND

tel. +358 20 553 41

fax +358 20 553 4207

www.koskisen.com

committedtoood.koskisen.com

